



NESTAFLEX

200 RLS GRAVITY ROLLER CONVEYOR

DETAILS

WIDTH: 18" / 24" / 30"

Determined by package size, available conveying area and application specific needs

LENGTH EXTENDED: 8' - 60'

Determine total length needed, including curvatures and obstructions

AXLE CENTER: 3" / 4" / 5.25"

Package size determines necessary axle center length on fully extended conveyor

ROLLER TYPE:

Zinc plated 1.375" steel rollers

Designed to expand, contract and move easily, the **NestaFlex® 200** is a self tracking, gravity roller conveyor that has a per linear foot capacity of 200 pounds. The all steel construction provides unmatched structural integrity, whether the conveyor is extended, contracted or configured in simple or compound curves.

This unit is engineered to handle odd shaped cartons, drums, and pails in low to medium volume applications. It is the best choice for moving items without a flat, solid surface.



C O N V E Y O R S

A DURAVANT COMPANY

NESTAFLEX

200 RLS GRAVITY ROLLER CONVEYOR

SPECIFICATIONS

| 18" WIDE MODELS | | 24" WIDE MODELS | | 30" WIDE MODELS | | LENGTH ADJUSTMENTS | |
|-----------------|----------|-----------------|----------|-----------------|----------|--------------------|----------|
| MODEL # | LEG SETS | MODEL # | LEG SETS | MODEL # | LEG SETS | CONTRACTED | EXTENDED |
| RLS18008S | 3 | RLS24008S | 3 | RLS30008S | 3 | 2' 5" | 8' 11" |
| RLS18012S | 4 | RLS24012S | 4 | RLS30012S | 4 | 3' 5" | 12' 10" |
| RLS18016S | 5 | RLS24016S | 5 | RLS30016S | 5 | 4' 5" | 16' 9" |
| RLS18020S | 6 | RLS24020S | 6 | RLS30020S | 6 | 5' 6" | 20' 9" |
| RLS18024S | 7 | RLS24024S | 7 | RLS30024S | 7 | 6' 7" | 24' 8" |
| RLS18028S | 8 | RLS24028S | 8 | RLS30028S | 8 | 7' 8" | 28' 5" |
| RLS18032S | 9 | RLS24032S | 9 | RLS30032S | 9 | 8' 9" | 32' 4" |
| RLS18036S | 10 | RLS24036S | 10 | RLS30036S | 10 | 9' 9" | 36' 3" |
| RLS18040S | 11 | RLS24040S | 11 | RLS30040S | 11 | 10' 10" | 40' 2" |

All conveyor products can be modified to suit specific design requirements. Please contact our sales representatives for details on sizes or options that are not listed.

STANDARD FEATURES

- Load capacity 200 lbs/ft
- Zinc plated 1.375" steel rollers
- 5.25" axle centers
- 28" – 44" adjustable conveyor heights using hand knobs to raise or lower the legs
- Heavy duty steel square tubing zinc plated legs
- Welded horizontal leg brace
- Heavy duty 5" x 1.5" casters with 2 total lock brake casters on each end
- 7 gauge steel side links assembled using shoulder bolts and locking nuts
- 5/16" Ø axles across the width
- Self-tracking
- Couplers
- Heavy duty retractable package stop

OPTIONS

- 4" and 3" axle centers
- Additional brake casters
- Additional set of couplers
- Elevations for Adjustable legs
20"-28"
25"-38"
36"-52"

ACCESSORIES

- Curve Guards

TECHNICAL DATA

CONSTRUCTION

All Steel Bolted Construction

LEGS

Zinc Plated, heavy-duty leg supports
1.125" square steel tubing with a double welded cross brace

SIDE LINKS

Made of 7 gauge steel

WARRANTY

MECHANICAL: 24 Months

SERVICES AVAILABLE

Technical Support
Installation & Setup
Service Maintenance
Application Support
Hardware Support



**NESTAFLEX® 200
COMPACTED**

800.327.9209 | FMHSALES@FMHCONVEYORS.COM | WWW.FMHCONVEYORS.COM



FMH CONVEYORS IS A MEMBER OF THE DURAVANT FAMILY OF COMPANIES

PACKAGING SOLUTIONS | FOOD PROCESSING SOLUTIONS | MATERIAL HANDLING SOLUTIONS | SUPPORTPRO

www.duravant.com