



AFTERSORT

TL2 RIGID TWO STAGE TRUCK LOADER

DETAILS

CONVEYOR IN-FEED WIDTH: 34"

CONVEYOR DISCHARGE WIDTH: 31"

LENGTH EXTENDED: UP TO 64'

Length is determined by specific application needs

The **AFTERSORT TL2** Extendible Telescoping Conveyor is built to withstand punishment in shipping areas that have a high degree of forklift traffic or other collision obstacles. If your business is spending valuable time and expense on maintaining your existing truck loaders, the TL2 Extendible Telescoping Conveyor is the solution.

This two-piece telescoping conveyor is constructed of a 10 inch structural steel channel framework with very few moving parts. Thus supplying your business years of virtually maintenance free operation. The Structural framework and 1.9 inch diameter by 16 gauge galvanized rollers are set low in the frame to create its own integral product guides. The frame itself is built to withstand collisions with forklifts, trailer walls and other obstacles in the shipping area.



C O N V E Y O R S

A DURAVANT COMPANY

AFTERSORT

TL2 RIGID TWO STAGE TRUCK LOADER

SPECIFICATIONS

STANDARD FEATURES

- Powered in and out at 45 FPM
- Power requirements 480 VAC 3 phase
- 1.5 HP drive motor and gearbox
- 2 stage extendable. Infeed stage 35" wide
Discharge stage 31" wide
- Elevations: Infeed 54" - Discharge 26"
- Decline needs 60" clear space
- Side guards to prevent carton spill
- 1.9" galvanized roller on 3" axle centers with
Lenze Reducer
- Includes floor mounted guide track
- 18-inch solid tires on drive axle and steering axle.
- 10" rigid casters on infeed end.
- Safety bumper bar on discharge end with auto
reverse
- 3 degrees steering in both directions at
discharge end
- Recessed control switches to reduce the
possibility of damage
- Guide wheel located at the discharge end to
align the conveyor with guide track
- Power and interlock feed to conveyor from
festoon with yellow cable

OPTIONS

- Light and Fan Kits
- 2" Roller Centers
- ABEC Sealed Precision Bearings
- 230VAC 3 Phase Power
- Herringbone Transition
- Operator Controls for Upstream
Conveyors
- Other Widths & Lengths Available

TECHNICAL DATA

CONSTRUCTION

All Steel Construction

TIRES

Large 18" Solid Rubber Tires

WARRANTY

ELECTRICAL: 12 Months

MECHANICAL: 24 Months

SERVICES AVAILABLE

Technical Support

Installation & Service

Preventative & Routine Maintenance

Application Support

Operator & Maintenance Training



800.327.9209 | FMHSALES@FMHCONVEYORS.COM | WWW.FMHCONVEYORS.COM



FMH CONVEYORS IS A MEMBER OF THE DURAVANT FAMILY OF COMPANIES

PACKAGING SOLUTIONS | FOOD PROCESSING SOLUTIONS | MATERIAL HANDLING SOLUTIONS | SUPPORTPRO

www.duravant.com