

LITESORT AUTOMATED SORTATION SYSTEM





LITESORT :: KEY BENEFITS



MODULAR DESIGN:: Sections are on casters for convenient relocation, and divert wings are foldable to reduce storage area and improve maneuverability

READY TO SCAN:: Scan and read barcodes to more accurately sort items with up to five side scanning

PLUG & PLAY :: Utilizes 110V power and simple 24V DC control systems

SIMPLE DEPLOYMENT:: No special tools or skills are required to build or operate the system



LITESORT :: EFFICIENCY GAINS



- Faster load / unload
- Reduced labor & number of touches
- Improved ergonomics
- Reduced walking for associates
- Faster training for associates
- Faster replenishment process
- Consistent product flow



LITESORT :: STANDARD SPECIFICATIONS



Load Capacity	50 lbs/ft	
Roller Size	1.9 in	
Roller Widths	30 in	
Standard Axle Centers	3 in	
Motor Driven Rollers	24V DC Brushless	
MDR Speeds	60 - 194 fpm	
Scannable Sides	Up to 5 sides	
System Sortation Rate	25 - 30 cartons per minute	

CONVEYABLE SIZES


	Length	Width	Height
Minimum	9 in	6 in	1 in
Maximum	48 in	25 in	24 in
Average	18 in	12 in	10 in



Conveyable sizes based off of configuration.

LITESORT :: SYSTEM OVERVIEW






LITESORT :: GAPPING & SCANNING



BELTED GAPPING MDR CONVEYOR



INTEGRATED SCAN TUNNEL


LITESORT :: GAPPING & SCANNING





BELTED MDR GAPPING CONVEYOR

Ensure proper gap between items going through the scanner




INTEGRATED SCAN TUNNEL

Scan up to five sides to automatically determine sort locations

LITESORT :: INTUITIVE CONTROLS








INTUITIVE INTERFACE & STACK LIGHT

Quickly know LITESORT is working at full capacity with convenient access to key operational and diagnostic information

LITESORT :: MODULAR SORTATION





LITESORT :: MODULAR SORTATION






MODULAR DESIGN ALLOWS COMPLETE CONTROL

- Sort to any number of wings
- Configure single or double gravity divert wings
- Sort to other conveyors like
 BestFlex or BestConnect


LITESORT :: DIVERTS & WINGS






LITESORT :: DIVERTS & WINGS





FOLDABLE GRAVITY DIVERT WINGS

Quickly fold for storage to maximize every square foot in your facility




BI-DIRECTIONAL POP-UP DIVERTS

24V All electric mechanism avoids the need for pneumatics

LITESORT :: BASE CONFIGURATION





LITESORT :: STANDARD SPECIFICATIONS



Load Capacity	50 lbs/ft	
Roller Size	1.9 in	
Roller Widths	30 in	
Standard Axle Centers	3 in	
Motor Driven Rollers	24V DC Brushless	
MDR Speeds	60 - 194 fpm	
Scannable Sides	Up to 5 sides	
System Sortation Rate	25 - 30 cartons per minute	

CONVEYABLE SIZES

	Length	Width	Height
Minimum	9 in	6 in	1 in
Maximum	48 in	25 in	24 in
Average	18 in	12 in	10 in



Conveyable sizes based off of configuration.